



Australia Power Cord, Type I, SAA, RCM certified 3 pins AS/NZS 3112 Plug to IEC 60320 C13 Left Angle Connector

Plug and Connector Type: I
Non-rewirable With Earthing Contact, Moulded.

Fully conforms to the AS/NZS 3112, IEC 60320 C13 plug standards and RoHS, REACH and PAHS compliant. Quality is stable and reliable!

- Electrical Rating: 10A
- Voltage: 250V
- Approvals: SAA, RCM Certified

Australia SAA Power Cords

Specifications

Label	Value
Approvals:	SAA, RCM
Plug / Connector Type:	I
Connector Standard:	AS/NZS 3112, IEC 60320 C13
Maximum Current rating:	10A
Maximum Voltage:	250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity

Available Wire Styles

Gauge/ # Conductors	Cord Type
3X0.75mm ²	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F
3x1.0mm ²	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F
3x1.5mm ²	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F

Our other certificated products

