



Indonesia Power Cord, Type E, F, SNI, VDE, TUV certified 3 pins CEE 7/7 straight Schuko Plug to IEC 60320 C13 Connector

Plug and Connector Type: E, F
Non-rewirable With Earthing Contact, Moulded.

Fully conforms to the CEE 7/7, SNI 04-3892, IEC 60320 C13 plug standards and RoHS, REACH and PAHS compliant. Quality is stable and reliable!

- Electrical Rating: 16A
- Voltage: 250V
- Approvals: SNI, VDE, TUV Certified

Indonesia SNI Power Cords

Specifications

| Label | Value |
|-------------------------------|--|
| Approvals: | SNI, VDE, TUV |
| Plug / Connector Type: | E, F |
| Connector Standard: | CEE 7/7, SNI 04-3892, IEC 60320 C13 |
| Maximum Current rating: | 16A |
| Maximum Voltage: | 250V |
| Number of Poles and Wires: | 3 poles, 3 wires |
| Copper Conductor Material: | Oxygen free Copper (OFCU) |
| Outer Jacket Material: | PVC, Rubber, Halogen-Free, Textile braid |
| Blade Material: | Nickel coated Brass |
| Flamability Rating: | UL 94V-0 |
| Color: | black is standard but any color available |
| Temperature Rating: | minus 40C though plus 75C |
| Environmental Certifications: | RoHS, REACH, PAHs |
| Testing: | Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity |

Available Wire Styles

| Gauge/ # Conductors | Cord Type |
|-----------------------|---|
| 3x0.5mm ² | H03VV-F |
| 3x0.75mm ² | H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-F |
| 3x1.0mm ² | H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F |
| 3x1.5mm ² | H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F |

Our other certificated products

