



**Israel Power Cord, Type H, SII certified 3 pins SI-32 Plug to IEC 60320 C13 Left Angle Connector**

Plug and Connector Type: H  
Non-rewirable With Earthing Contact, Moulded.

Fully conforms to the SI-32, IEC 60320 C13 plug standards and RoHS, REACH and PAHS compliant. Quality is stable and reliable!

- Electrical Rating: 10A
- Voltage: 250V
- Approvals: SII Certified

**Israel SII Power Cords**

**Specifications**

Label	Value
Approvals:	SII
Plug / Connector Type:	H
Connector Standard:	SI-32, IEC 60320 C13
Maximum Current rating:	10A
Maximum Voltage:	250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity

**Available Wire Styles**

Gauge/ # Conductors	Cord Type
3x0.5mm <sup>2</sup>	H03VV-F
3x0.75mm <sup>2</sup>	H03VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-F
3x1.0mm <sup>2</sup>	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F
3x1.5mm <sup>2</sup>	H05VV-F, H05RR-F, H05RN-F, H03RT-F, H07RN-F

**Our other certificated products**

