



Swiss Power Cord, Type C, SEV certified 2 pins SN 441011 Plug to IEC 60320 C7 Connector

Plug and Connector Type: C
Non-rewirable With Earthing Contact, Moulded.

Fully conforms to the SN 441011, IEC 60320 C7 plug standards and RoHS, REACH and PAHS compliant. Quality is stable and reliable!

- Electrical Rating: 2.5A
- Voltage: 250V
- Approvals: SEV Certified

Swiss SEV Power Cords

Specifications

Label	Value
Approvals:	SEV
Plug / Connector Type:	C
Connector Standard:	SN 441011, IEC 60320 C7
Maximum Current rating:	2.5A
Maximum Voltage:	250V
Number of Poles and Wires:	2 poles, 2 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Environmental Certifications:	RoHS, REACH, PAHS
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity

Available Wire Styles

Gauge/ # Conductors	Cord Type
2x0.5mm ²	H03VV-F, H03VVH2-F
2x0.75mm ²	H03VV-F, H03VVH2-F, H05VV-F, H05VVH2-F, H05RR-F, H05RN-F, H03RT-H, H05V2V2-F
2x1.0mm ²	H05VV-F, H05VV-F, H05RR-F, H05RN-F, H03RT-H, H05V2V2-F
2x1.5mm ²	H05VV-F, H05VV-F, H05RR-F, H05RN-F, H07RN-F, H03RT-H, H05V2V2-F

Our other certificated products

